



KONE MONOSPACE[®] 700

MACHINE AT SIDE CONFIGURATION & DIMENSIONS

Available in passenger and service shape with front and rear opening options

Max Travel

300 ft. (91.4 m)

Max Landings

36

Speed

200, 350, 500 fpm

(1.00, 1.78, 2.54 m/s)

Car Height **F**

8, 9 or 10 ft.

(2438, 2743 or

3048 mm)

Entrance Height **G**

7, 8 or 9 ft.

(2134, 2438 or 2743 mm)

			A	A SEISMIC	B	B SEISMIC	C	D	E
	CAPACITY lbs. (kg)	OPENING TYPE	HOISTWAY WIDTH (mm)	HOISTWAY WIDTH (mm)	HOISTWAY DEPTH (mm)	HOISTWAY DEPTH (mm)	INTERIOR WIDTH (mm)	INTERIOR DEPTH (mm)	DOOR WIDTH (mm)
Front Opening PASSENGER	2500 (1134)	SSP-CO	9'-5" (2870)	9'-9" (2972)	6'-10" (2083)	7'-1" (2159)	6'-8½" (2045)	4'-3¼" (1302)	3'-6" (1067)
	3000 (1361)	SSP-CO	9'-5" (2870)	9'-9" (2972)	7'-1" (2159)	7'-4" (2235)	6'-8½" (2045)	4'-9¼" (1454)	3'-6" (1067)
	3500 (1588)	SSP-CO	9'-5" (2870)	9'-9" (2972)	7'-5" (2261)	7'-8" (2337)	6'-8½" (2045)	5'-5¼" (1657)	3'-6" (1067)
	4000 (1814)	CO	10'-5" (3175)	10'-9" (3277)	7'-5" (2261)	7'-8" (2337)	7'-8½" (2350)	5'-5¼" (1657)	4'-0" (1219)
Front Opening SERVICE	4000 (1814)	2SP	8'-5" (2565)	8'-9" (2667)	9'-5" (2870)	9'-8" (2946)	5'-8½" (1740)	7'-6" (2286)	4'-0" (1219)
	4500 (2041)	2SP	8'-5" (2565)	8'-9" (2667)	9'-11" (3023)	10'-2" (3099)	5'-8½" (1740)	8'-0" (2438)	4'-0" (1219)
	5000 (2268)	2SP	8'-5" (2565)	8'-9" (2667)	10'-2" (3099)	10'-5" (3175)	5'-8½" (1740)	8'-7¾" (2635)	4'-6" (1372) ⁽⁹⁾
	5000 AIA (2268)	2SP	8'-5" (2565)	8'-9" (2667)	10'-7¾" (3245)	10'-10¾" (3321)	5'-8½" (1740)	9'-0" (2743)	4'-6" (1372) ⁽⁹⁾
Front & Reverse Opening PASSENGER	2500 (1134)	SSP-CO	9'-5" (2870)	9'-9" (2972)	7'-1" (2159)	7'-1" (2159)	6'-8½" (2045)	4'-3¼" (1314)	3'-6" (1067)
	3000 (1361)	SSP-CO	9'-5" (2870)	9'-9" (2972)	7'-6" (2286)	7'-6" (2286)	6'-8½" (2045)	4'-9¼" (1467)	3'-6" (1067)
	3500 (1588)	SSP-CO	9'-5" (2870)	9'-9" (2972)	7'-9½" (2375)	7'-9½" (2375)	6'-8½" (2045)	5'-5¼" (1670)	3'-6" (1067)
	4000 (1814)	CO	10'-5" (3175)	10'-9" (3277)	7'-9½" (2375)	7'-9½" (2375)	7'-8½" (2350)	5'-5¼" (1670)	4'-0" (1219)
Front & Reverse Opening SERVICE	4000 (1814)	2SP	8'-5" (2565)	8'-9" (2667)	10'-1" (3073)	10'-1" (3073)	5'-8½" (1740)	7'-6½" (2299)	4'-0" (1219)
	4500 (2041)	2SP	8'-5" (2565)	8'-9" (2667)	10'-7" (3226)	10'-7" (3226)	5'-8½" (1740)	8'-0½" (2451)	4'-0" (1219)
	5000 (2268)	2SP	8'-5" (2565)	8'-9" (2667)	11'-2¾" (3422)	11'-2¾" (3422)	5'-8½" (1740)	8'-8¼" (2648)	4'-6" (1372) ⁽⁹⁾
	5000 AIA (2268)	2SP	8'-5" (2565)	8'-9" (2667)	11'-6¾" (3524)	11'-6¾" (3524)	5'-8½" (1740)	9'-0" (2743)	4'-6" (1372) ⁽⁹⁾

CLEAR OVERHEAD **H** AND PIT DEPTH **I**

CAPACITY lbs. (kg)	200 FPM (1.00 M/S)		350 FPM (1.78 M/S)		500 FPM (2.54 M/S)	
	PIT DEPTH (mm)	CLEAR OVERHD (mm)	PIT DEPTH (mm)	CLEAR OVERHD (mm)	PIT DEPTH (mm)	CLEAR OVERHD (mm)
2500 (1134)	5'-3" (1600)	13'-7" (4140)	5'-5" (1651)	13'-11" (4242)	5'-5" (1651)	13'-11" (4242)
3000 (1361)	5'-5" (1651)	13'-7" (4140)	5'-5" (1651)	14'-4" (4369)	5'-5" (1651)	14'-4" (4369)
3500 (1588)	5'-5" (1651)	13'-7" (4140)	5'-5" (1651)	14'-9" (4496)	5'-5" (1651)	14'-9" (4496)
4000 (1814)	5'-8" (1727)	13'-7" (4140)	5'-8" (1727)	14'-11" (4547)	7'-3" (2210)	15'-8" (4775)
4500 (2141)	5'-8" (1727)	14'-9" (4496)	5'-11" (1803)	15'-3" (4648)	7'-6" (2286)	16'-0" (4877)
5000 – 5000 AIA (2268)	5'-11" (1803)	15'-2" (4623)	5'-11" (1803)	15'-11" (4551)	—	—

Visit kone.us for the latest project-specific details, BIM Models, CAD drawings, specifications, electrical data, reaction loads and building access requirements.



CONTROL SPACE

CAPACITY lbs. (kg)	CONTROLLER SPACE	J WIDTH (mm)	K DEPTH (mm)	L DOOR WIDTH (mm)
2500 to 5000 AIA (1134 to 2268)	integral or remote cabinet	4'-4" (1321)	1'-8" (508)	4'-0" (1219)
2500 to 5000 AIA (1134 to 2268)	adjacent or remote room	5'-0" (1524)	dimension (B)	3'-0" (914)

Notes

- (1) Smaller pit and overhead dimensions may be available per specific applications. Contact your KONE Sales Professional for further information.
- (2) Buffer service platforms are required when pit depth exceeds 8'-6" (2590 mm).
- (3) A hoist beam (by KONE) is required for installation (by others). Dimension **H** reflects clear under hoist beam.
- (4) If occupied space exists below the hoistway, consult your KONE Sales Professional.
- (5) All dimensions are based on an 8'-0" (2438 mm) cab with a 7'-0" (2134 mm) door. Alternate car and door heights are available, but will affect dimension **H**.
- (6) If an Emergency Battery Device (EBD) is required, please contact your KONE Sales Professional for further details regarding dimensions **J** and **L**.
- (7) Contact your local KONE Sales Professional regarding local code variations when utilizing the integral and remote closet options.
- (8) If utilizing KONE Polaris™ destination control system or KONE Access™, contact your local KONE Sales Professional regarding control space size requirements.
- (9) 4'-0" (1219 mm) door width also available.

Plan views



Section view

